

**TopGard® Acrylic Elastomeric Roof Coating – Base Coat**

Version 2.2

Revision Date 06/26/2020

Print Date 06/26/2020

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Trade name : TopGard® Base Coat

## Manufacturer or supplier's details

Company : Johns Manville  
Address : P.O. Box 5108  
Denver, CO USA 80127  
Telephone : +1-303-978-2000  
Emergency telephone : 24-Hour Number: 1-800-424-9300 (CHEMTREC)  
number

Company : Johns Manville Canada Inc.  
Address : 5301 42 Avenue  
Innisfail, AB Canada T4G 1A2  
Telephone : +1-303-978-2000  
Emergency telephone : 24-Hour Number: 1-800-424-9300 (CHEMTREC)  
number

Recommended use of the chemical and restrictions on use

Restrictions on use : For professional and industrial installation and use only.

Prepared by : productsafety@jm.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015)**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous components**

Chemical name	CAS-No.	Concentration (%)
limestone	1317-65-3	>= 15 - <= 40
titanium dioxide	13463-67-7	>= 3 - <= 7
quartz (SiO <sub>2</sub> )	14808-60-7	>= 0.1 - < 1

Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

General advice : Handle in accordance with good industrial hygiene and safety practice.

**TopGard® Acrylic Elastomeric Roof Coating – Base Coat**

Version 2.2

Revision Date 06/26/2020

Print Date 06/26/2020

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
- In case of skin contact : In case of contact, flush skin with plenty of water for at least 5 minutes.  
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 5 minutes.  
If easy to do, remove contact lens, if worn.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Gently wipe or rinse the inside of the mouth with water.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician or Poison Control Centre immediately.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Foam  
Water spray
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Vapours may form flammable mixture with air  
Vapours are heavier than air and may spread along floors.  
The product will float on water and can be reignited on surface water.  
Flash back possible over considerable distance.
- Hazardous combustion products : carbon oxides  
Silicon oxides  
titanium/titanium oxides  
Acrylic monomers
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

## TopGard® Acrylic Elastomeric Roof Coating – Base Coat

Version 2.2

Revision Date 06/26/2020

Print Date 06/26/2020

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Clean contaminated floors and objects thoroughly while observing environmental regulations.  
The product should not be allowed to enter drains, water courses or the soil.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

- Local/Total ventilation : Do not use in areas without adequate ventilation.
- Advice on protection against fire and explosion : Vapours may form explosive mixtures with air.  
Vapours are heavier than air and may spread along floors.
- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.  
To maintain product quality, do not store in heat or direct sunlight.
- Materials to avoid : No materials to be especially mentioned.
- Recommended storage temperature : 4 - 38 °C
- Storage period : 12 Months
- Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
limestone	1317-65-3	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA
		TWA	5 mg/m <sup>3</sup>	OSHA

**TopGard® Acrylic Elastomeric Roof Coating – Base Coat**

Version 2.2

Revision Date 06/26/2020

Print Date 06/26/2020

		(respirable fraction)		
		TWA (respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA
		TWA	10 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
quartz (SiO <sub>2</sub> )	14808-60-7	TWA (Respirable fraction)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA

**Engineering measures** : Use a local and/or general ventilation system.  
Provide exhaust ventilation close to floor level.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection  
Material : Protective gloves

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Wear protective clothing, such as long-sleeved shirts and pants.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
Written instructions for handling must be available at the work place.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**TopGard® Acrylic Elastomeric Roof Coating – Base Coat**

Version 2.2

Revision Date 06/26/2020

Print Date 06/26/2020

Appearance	: liquid
Colour	: off-white
Odour	: amine-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: 0 °C
Boiling point/boiling range	: 100 °C
Flash point	: No flash point was obtained, but the product may release flammable vapour.
Evaporation rate	: Same as water
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 24.8 hPa (21 °C)
Relative vapour density	: > 1 (Air = 1.0) Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density	: 1.03 (Water = 1.0)
Solubility(ies)	
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: 1,700 - 2,600 mPa.s
Viscosity, kinematic	: No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous	: No hazards to be specially mentioned.

**TopGard® Acrylic Elastomeric Roof Coating – Base Coat**

Version 2.2

Revision Date 06/26/2020

Print Date 06/26/2020

reactions

- Conditions to avoid : None known.
- Incompatible materials : No data available
- Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:  
 carbon oxides  
 Silicon oxides  
 titanium/titanium oxides  
 Acrylic monomers

**SECTION 11. TOXICOLOGICAL INFORMATION**
**Acute toxicity**
**Product:**

- Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
 Method: Calculation method
- Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Method: Calculation method
- Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
 Method: Calculation method

**Acute toxicity**
**Components:**
**limestone:**

- Acute oral toxicity : LD0 (Rat, female): > 2,000 mg/kg  
 Method: OECD Test Guideline 420
- Acute inhalation toxicity : LC50 (Rat, male and female): > 3 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Method: OECD Test Guideline 403  
 Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg  
 Method: OECD Test Guideline 402

**Acute toxicity**
**titanium dioxide:**

- Acute oral toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat, male and female): > 5.09 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Method: OECD Test Guideline 403

**TopGard® Acrylic Elastomeric Roof Coating – Base Coat**

Version 2.2

Revision Date 06/26/2020

Print Date 06/26/2020

Acute dermal toxicity : Method: Expert judgement  
 Assessment: The substance or mixture has no acute dermal toxicity

**Acute toxicity**
**quartz (SiO<sub>2</sub>):**

Acute oral toxicity : LD50 (Rat): > 22,500 mg/kg

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

**IARC**

Group 1: Carcinogenic to humans

quartz (SiO<sub>2</sub>) 14808-60-7

Group 2B: Possibly carcinogenic to humans

titanium dioxide 13463-67-7

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA (29 CFR 1910 Subpart Z, Toxic and Hazardous Substances).

**NTP**

Known to be human carcinogen

quartz (SiO<sub>2</sub>) 14808-60-7

---

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**
**Components:**
**quartz (SiO<sub>2</sub>):**

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 10,000 mg/l  
 Exposure time: 72 h

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**
**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

**TopGard® Acrylic Elastomeric Roof Coating – Base Coat**

Version 2.2

Revision Date 06/26/2020

Print Date 06/26/2020

Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : Harmful to aquatic life.  
Harmful to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.  
The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Packaging that cannot be reused after cleaning must be disposed or recycled in accordance with all federal, national and local regulations.

**SECTION 14. TRANSPORT INFORMATION****International transport regulations**

Land transport

USDOT: Not classified as a dangerous good under transport regulations

TDG: Not classified as a dangerous good under transport regulations

Sea transport

IMDG: Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO: Not classified as a dangerous good under transport regulations

**SECTION 15. REGULATORY INFORMATION****TSCA list**

TSCA - 5(a) Significant New Use Rule List of Chemicals : No substances are subject to a Significant New Use Rule.

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : No substances are subject to TSCA 12(b) export notification requirements.

**EPCRA - Emergency Planning and Community Right-to-Know Act**



**TopGard® Acrylic Elastomeric Roof Coating – Base Coat**

Version 2.2

Revision Date 06/26/2020

Print Date 06/26/2020

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ammonia, aqueous solution	1336-21-6	1000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

**California Prop. 65**

This product does not require a warning under the California Safe Drinking Water and Toxic Enforcement Act (Proposition 65).

**The components of this product are reported in the following inventories:**

TSCA : On the inventory, or in compliance with the inventory

DSL : On the inventory, or in compliance with the inventory

**SECTION 16. OTHER INFORMATION**
**Further information**

Revision Date : 06/26/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.